

Beautiful Pictures for You


Face Detection with Auto Red-Eye Removal

Face Detection identifies faces and optimizes focus and exposure, making people pictures a snap. Selectable red-eye removal detects and compensates for red-eye in detected faces, for flattering flash portraits and party pictures.

○ Face Detection



Lost Photo Opportunity




FinePix J15fd

○ Auto Red-Eye Removal



Lost Photo Opportunity



FinePix J15fd

Styling for You

Slim Body & Stylish Design

In a choice of silver or black, and with its own handy soft case*, the slim, stylish FinePix J15fd slips effortlessly into your purse or pocket and goes everywhere with ease.

*Included



SPECIFICATIONS

FinePix J15fd

Number of effective pixels*	8.2 million pixels
CCD sensor	1/2.5-inch CCD
Storage media	Internal memory (approx. 8MB) / xD-Picture Card™ (16MB - 2 GB) / SD / SDHC memory card*
File format	Still image: JPEG (Exif Ver. 2.2*) / Movie: AVI (Motion JPEG) with sound [Design rule for Camera File system compliant / DPOF-compatible]
Number of recorded pixels	Still image: 3,264 × 2,448 (8M) / 3,264 × 2,176 (3:2 format) / 2,304 × 1,728 / 1,600 × 1,200 / 640 × 480
Lens	Fujinon 3× optical zoom lens
Lens focal length	f=6.2 - 18.6mm, equivalent to 38 - 113mm on a 35mm camera
Digital zoom	Approx. 5.1×
Aperture	F2.8 - F5.6 (W) / F5.2 - F10.4 (T)
Focus distance (from lens surface)	Normal: Approx. 40cm / 1.3 ft. to infinity Macro: Wide: Approx. 15cm / 5.9 in. to infinity Telephoto: Approx. 40cm / 1.3 ft. to infinity
Sensitivity	Auto / Equivalent to ISO 64 / 100 / 200 / 400 / 800 / 1600 (Standard Output Sensitivity)
Exposure control	TTL 256-zones metering
Exposure mode	Programmed AE
Shooting modes	Auto, Manual, Picture Stabilization (Anti-blur), Movie SP: Natural Light, Baby, Portrait, Landscape, Sport, Night, Beach, Snow, Fireworks, Sunset, Flower, Party, Museum, Text
Shutter speed	(Auto mode) 1/4 sec. to 1/2000 sec., (All other modes) 8 sec. to 1/2000 sec.
Continuous shooting	Top-3
Focus	Auto focus (Center)
White balance	Automatic scene recognition Preset: Fine, Shade, Fluorescent light (Daylight), Fluorescent light (Warm white), Fluorescent light (Cool white), Incandescent light
Self-timer	Approx. 10 sec. / 2 sec. delay
Flash	Auto flash Flash modes Red-eye removal OFF: Auto, Forced Flash, Suppressed Flash, Slow Synchro. Red-eye removal ON: Red-eye Reduction Auto, Red-eye Reduction & Forced Flash, Suppressed Flash, Red-eye Reduction & Slow Synchro.
LCD monitor	2.5-inch, Approx. 153,000 dots, TFT color LCD monitor, Approx. 96% coverage 640 × 480 pixels, 320 × 240 pixels (30 frames/sec.) with monaural sound
Movie recording	640 × 480 pixels, 320 × 240 pixels (30 frames/sec.) with monaural sound
Photography functions	Face Detection (with Auto red-eye removal), Best framing, Frame No. memory
Playback functions	Face Detection (with Red-eye removal), Slide show, Trimming, Single frame, Multi-frame playback, Sorting by date, Image rotate
Video output	NTSC / PAL selectable
Digital input / output	USB 2.0 High-speed
Power source	NP-45 Li-ion battery (included)
Dimensions	91.0 (W) × 55.0 (H) × 22.0 (D)* mm / 3.8 (W) × 2.2 (H) × 0.9 (D)* in. (excluding accessories and attachments) *Measures a mere 19.0 mm/0.75 inches at its slimmest point.
Weight	Approx. 110g / 3.9 oz. (excluding accessories, batteries and memory card)
Accessories included	Li-ion battery NP-45, Battery charger BC-45A or BC-45, Soft case, Hand strap, AV cable, USB cable, CD-ROM: FinePixViewer S / FinePixViewer, Owner's manual (CD-ROM), Basic manual
Optional accessories*	xD-Picture Card™: DPC-M512 (512MB), DPC-MP1GB (1GB), DPC-MP2GB (2GB) Li-ion battery NP-45, Battery charger BC-45, Waterproof case WP-FXJ10, PC card adapter DPC-AD, Compact Flash™ card adapter DPC-CF

Number of images / recording time

Modes	Still image						Movie	
Number of recorded pixels	3,264 × 2,448	3,264 × 2,176 (3:2 format)	2,304 × 1,728	1,600 × 1,200	640 × 480		Movie recording time	
Quality	JPEG Fine	JPEG Normal	JPEG	JPEG	JPEG	JPEG	VGA(30 fps)	QVGA(30 fps)
Internal memory (approx. 8MB)	1	2	3	6	10	35	4 sec.	9 sec.
xD-Picture Card™ 256MB	61	110	121	231	339	1,186	3.5 min.	7.4 min.
512MB	124	221	242	463	680	2,374	7 min.	14.9 min.
1GB	249	444	486	929	1,363	4,757	14.1 min.	30.1 min.
2GB	498	889	974	1,860	2,728	9,519	28.3 min.	60.3 min.
SD memory card 512MB	120	214	235	449	659	2,299	6.8 min.	14.5 min.
1GB	241	430	471	900	1,320	4,607	13.7 min.	29.1 min.
2GB	483	861	943	1,802	2,643	9,221	27.5 min.	58.4 min.
SDHC memory card 4GB	968	1,725	1,890	3,609	5,293	18,467	55.1 min.*	117 min.*
8GB	1,924	3,463	3,793	7,242	10,622	37,056	110.6 min.*	234.9 min.*

Actual number of frames and recording time varies depending on the types of memory card or shooting conditions.

*A movie recording will stop automatically when the movie file size becomes approx. 2GB.

*1 Number of effective pixels: The number of pixels on the image sensor which receive input light through the optical lens, and which are effectively reflected in the final output data of the still image.

*2 Please see the Fujifilm website to check memory card compatibility.

*3 Exif 2.2 is a digital camera file format that contains a variety of shooting information for optimal printing.

*4 Accessory availability may vary by country. Please check with your local Fujifilm representative to confirm product availability.



Microsoft, Windows, and Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh and Mac OS are trademarks of Apple Computer, Inc., registered in the U.S. and other countries. xD-Picture Card™, SD logo and all other trademarks are the property of their respective holders.

For more information, please visit our Website:

http://www.fujifilm.com/products/digital_cameras/index.html

Specifications are subject to change without notice.
All sample photos are simulated images.

© 2008 FUJIFILM Corporation

FUJIFILM

FINEPIX J15fd

NEW



Slim & Stylish
with Face Detection



Soft Case
Included

8.2 Megapixels

3x Optical Zoom

Face Detection with
Auto Red-Eye Removal

Great Photos Made Easy for You: FinePix J15fd



Quality for You

8.2 Megapixels

With an impressive 8.2 megapixels of resolution, the FinePix J15fd promises pictures that are sharp, clear, and vivid, perfect for enlarged display or printing.

Features for You

3x Optical Zoom Lens

Featuring a 3x optical zoom, this compact performer lets you enjoy a range of picture-taking options, from atmospheric wide-angle scenes to dramatic close-ups.



Wide angle



2x optical zoom



3x optical zoom

High Sensitivity ISO 1600

ISO 1600 sensitivity ensures blur-free photos, even in low light or with rapidly moving subjects. It also lets you shoot without the flash, for attractive, natural-looking pictures that preserve the atmosphere and colors of the scene.

Picture Stabilization/Anti-blur Mode

Picture Stabilization Mode (Anti-blur mode) automatically corrects for camera shake and subject blur, helping you to capture fleeting moments in crisp stop-action with background detail intact.



Conventional digital camera



FinePix J15fd

FINEPIX J15fd



Black

Silver

Usability for You

Versatile Shooting Modes

An extensive selection of pre-programmed shooting modes ensures great photos in various conditions, eliminating the need to fuss with camera settings while delivering optimum results.

Auto	Manual	Landscape	Sport	Night	Natural Light
Beach	Snow	Fireworks	Sunset	Flower	Party
Museum	Baby	Portrait	Text	Anti-blur	Movie



Baby



Sunset



Flower

On-Screen Shooting Guide

Featuring explanations for each shooting mode, scene position, and control setting, the easy-to-read icon-based interface is designed to take the guesswork out of selecting camera settings.



2.5-inch LCD

The 2.5-inch LCD is big and bright, making it easy to compose attractive shots.

Additional Features

- Movie recording with sound
- xD/SD compatible slot



Optional Waterproof Case (WP-FXJ10)

Rated maximum depth: Approx. 3.0m (9.8 ft.)

Enjoy underwater shooting with waterproof case WP-FXJ10.

Accessory availability may vary by country. Please check with your local Fujifilm representative to confirm product availability.

